

ICEU86

Also available in the self-contained range for "Gourmet" cube: ICEU 36, ICEU 46, ICEU 66, ICEU 126, ICEU 146 See pertaining literature for more details







ICEU 86 AS/WS

ICE-O-Matic equipment range is the newly released EU made ice makers for Thimble-shaped rounded ice cubes coming from ICE-O-Matic.

Built in the Italian manufacturing plant of Frimont Spa, ISO 9001 Certified, these units are built with sturdy, corrosion resistant stainless steel, and feature European made componentry to assure maximum quality and reliability. Tested one by one, the ICE-O-Matic self contained units feature well balanced

contained units feature well balanced ratio between production and storage capacity, alongside with reduced outer dimensions that allow for built-in installations.

Front air louvers assure appropriate airflow in critical install requirements. Contemporary, elegant design unites excellent operational features with the reliability obtained through years of successful experience in ice making technology.

Insulated bin door and ice storage bin minimize air condensation and water formation on equipment surfaces. Electromechanic controls maximise reliability and ease of repair during the entire life of the equipment.

2014 FUNCTIONALITY IMPROVEMENTS:

- Improved water distribution system alongside with evaporator assembly: a larger number of ice cubes is now produced per each cycle, while the newly designed water distribution spray system provides best evaporator surface coverage and is simple to remove during routine cleaning.
- ✓ Optimized dimensions and production/ storage ratios. Easier to fit even under lowest bar counters and in reduced footprint spaces.
- Front panel installed thermostatic controls for ice cube size and storage bin ice level sensor. Easily accessible, allow for an easy adjustment of the key working parameters of the machine.
- ✓ Bin door slide rollers for a smooth openclose movement, with door movement rubber, sound dampening, shock absorbers.
- ✓ Utilities connection may run through side panel openings, for a reduced depth installation requirement.




ICEU86

Also available in the self-contained range for "Gourmet" cube: ICEU 36, ICEU 46, ICEU 66, ICEU 126, ICEU 146 See pertaining literature for more details





		570 mm (22 7/16")
690 mm (27 3/16")	688.5 mm (27 1/8")	
	1.5 mm (1/16")	



OPERATING LIMITS						
Air Temp. Range	10°C - 43°C					
Water Temp. Range	5°C - 38°C					
Water Pressure	Min. 0.8 bar Max. 5 bar					
Electrical Voltage	230V/50Hz/1ph (230V/60Hz/1ph on selected models)					

All specifications and performance data are subject to normal manufacturing variances.

All panels are in stainless steel.





Air out

570 mm

3/4" GAS WATER INLET WATER COOLDED ONLY 920 mm (3/16") WATER OUTLET 3/4" GAS WATER INLET CORD SET		ADJUSTABLE FEET				
40.5 mm (1 5/8") 94 mm (3 11/16") 94 mm (3 11/16") 3/4" GAS WATER INLET WATER COOLDED ONLY Ø20 mm (3/16") WATER OUTLET 3/4" GAS WATER INLET						
3/4" GAS WATER INLET WATER COOLDED ONLY Ø20 mm (3/16") WATER OUTLET 3/4" GAS WATER INLET						
3/4" GAS WATER INLET	3/4" GAS W	94 mm (3 11/16") VATER INLET WATER COOLDED ON	ILY	153 mm (6")	190 mm (7 1/2")	
		Ø20 mm (3/16") WATE	R OUTLET			
CORD_SET		3/4" GAS				
			CORD SET			

	ORDERING AND SPECIFICATION INFORMATION									
Model No.	Cond. unit	ICE Production per 24 hrs. at 10°C Air/10°C Water kg	ICE Production per 24 hrs. at 21°C Air/15°C Water kg	Bin storage kg	Voltage Characteristics	Refrigerant	Water Consumption I/h*	Electric Consumption kWh/24h*	Net Weight kg	Max. Shipping Weight kg
ICEU 86 AS	Air	39	35	15	230/50/1	R404A	5,2	9,3	35	41
ICEU 86 WS	Water	38	34	15	230/50/1	R404A	56,2	7,9	35	41

*measured t 32°C air / 21°C water

