



ELEVATION SERIES CUBE ICE MAKER CIMO635



Model:

□ CIMO635



CIMO635 ON CIB230

Features and Benefits

- 30" (768 mm) wide space-saving design.
- Produces up to 265kg of ice per day.
- *Energy and Environment*
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
 - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - Built in Agion® ensures unbeatable antimicrobial protection.
 - Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling.
 - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

CIMO635 CUBE ICE MAKER

Ice Form

FULL CUBE DIMENSIONS	
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (mm)	10 x 22 x 22



CUBE

Bin Chart *Kits for Combining Wider Bins with Smaller Models*

ICE STORAGE BINS								
	Model No.	B25	B40	B42	B55	CIB230	CIB400	B110
	Capacity Width	110 kg 762 mm	156 kg 762 mm	160 kg 559 mm	232 kg 762 mm	232 kg 770 mm	400 kg 1,220 mm	388 kg 1,219 mm
Kits	CIMO635	Kit Not Required		N/A	Kit Not Required		BT100	BPF-1

*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIMO635	CD10	CD100

Note: All modular cube CIM units can be installed with the O₃-Matic™ Ozone Delivery System.

Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts



ELEVATION SERIES CUBE ICE MAKER CIMO635





CIMO635 CUBE ICE MAKER

Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust. Top louvers must not be blocked more than 75%.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".

Dual Exhaust for Installation Flexibility



Air Cooled

Operating Requirements

	MINIMUM	MAXIMUM
		50Hz
Ambient Temp. Range Air	10 °C	43 °C
Water Temp.	4.4 °C	
Water Pressure	1.4 BAR	5.5 BAR

Dimensions

ALL MODELS	
W x D x H (mm)	768 x 616 x 540

Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage litres per 45 kg of Ice 32°C air/21°C water		kWH Used per 45 kg of ice @ 32°C air/ 21°C water	Watts Used Per Hr @ 32°C air/ 21°C water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
		21°C air/ 10°C water (kg)	32°C air/ 21°C water (kg)	Potable	Condenser						
CIMO635A	Air	265	204	20.0	-	572	1080	220-240/50/1	8.1	16	8,600

* Daily ice production based on half cube configuration.

Notes:
 Number of Wires: 3 (including ground)
 Approx. Shipping Weight kg: CCIMO635A 72.5
 Refrigerant Type: R404A

★ENERGY STAR qualified machine. Please see our website www.iceomatic.com for the latest list of ENERGY STAR qualified machines and available rebates